



## Application Gun for AEROSANA® VISCONN

AEROFIXX is a spray gun for quick and easy application of the AEROSANA® VISCONN and AEROSANA® VISCONN FIBRE sausages onto surfaces such as timber, wood fibre boards, OSB, stone, plaster, concrete, etc.

- ✓ Easy, one step application
- ✓ 2 separate settings allow for precise detailing as well as over spraying to seal surfaces.
- ✓ Simple clean-up after use
- ✓ Allows the installer to work with one hand
- ✓ No brush required
- ✓ Pressure: up to 6.8 bar (100 psi)

Tested for harmful substances  
in accordance with  
  
Based on the criteria of the Committee  
for Health-Related Evaluation of  
Construction Products at the German  
Federal Environment Agency



11 2024



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)





## Application Gun for AEROSANA® VISCONN

### Technical Data

Material	Stable aluminium pressure cylinder, ergonomic nylon handle
Colour	Black, grey
Operation pressure	Up to 6.8 bar (100 psi)
Air flow rate	300 l/min

### WEATHER EXPOSURE

Suitable to use outdoors in protected areas.

### APPLICATION NOTES

The AEROFIXX device should be connected to a compressor with a suction flow rate of >300 l/min. The pressure is set to 6 bar (87 psi). All AEROSANA® VISCONN products in 600ml sausages can be applied using the AEROFIXX device. The AEROFIXX tool comes with different air nozzles for different types of application. The adjustment ring under the spray nozzle allows you to easily switch between "line application" and "spray application" by turning the spray head. Cleaning is easily done with a damp cloth and/or warm water.

### Delivery Form

ID CODE	Forms of delivery	Weight	Sales unit
1AR02714	1 piece	1.6 kg	1



NEW ZEALAND  
0800 PRO CLIMA (776 254)  
Technical: [support@proclima.co.nz](mailto:support@proclima.co.nz)  
General: [welcome@proclima.co.nz](mailto:welcome@proclima.co.nz)  
[www.proclima.co.nz](http://www.proclima.co.nz)

AUSTRALIA  
1800 PRO CLIMA (776 254)  
[support@proclima.com.au](mailto:support@proclima.com.au)  
[welcome@proclima.com.au](mailto:welcome@proclima.com.au)  
[www.proclima.com.au](http://www.proclima.com.au)

