

Fleece for covering cracks and joints

AEROSANA FLEECE is a supplementary product for working with spray-on or brush-on seals from the AEROSANA VISCONN family. It can be used to reliably cover cracks or joints that are wider than 3 mm in the case of AEROSANA VISCONN or 20 mm in the case of AEROSANA VISCONN FIBRE. It is very useful for difficult junctions in mass timber, timber frame, commercial steel frames, concrete and masonry constructions.

- Reliable airtightness and windtightness
- Particularly effective on junctions & detailed features
- Very malleable fleece material
- Excellent values in hazardous substance test



11 2024



NEW ZEALAND 0800 PRO CLIMA (776 254) Technical: support@proclima.co.nz General: welcome@proclima.co.nz www.proclima.co.nz AUSTRALIA 1800 PRO CLIMA (776 254) support@proclima.com.au welcome@proclima.com.au www.proclima.com.au





Fleece for covering cracks and joints

Technical Data

Technical Data		
Material	PET	
Colour	White	
Surface weight	63 g/m²	
Thickness	0.7mm	
Tensile strength MD/CD	90 N/5 cm / 145 N/5 cm	
Elongation MD/CD	75% / 90%	
Application temperature	5°C to 60°C	
Coverage	3.75 m²/Roll	

IMPORTANT INFORMATION

- Airtightness even with geometrically challenging joints
- Seal pipes and other penetrations
- Holes of up to 70mm diameter can be sealed

WEATHER EXPOSURE

Suitable to use outdoors in protected areas in accordance with the AEROSANA® VISCONN system

APPLICATION NOTES

AEROSANA FLEECE can be used on subsurfaces that are slightly uneven and/or structured. To achieve airtight and/or windtight installation it is important that AEROSANA® FLEECE is coated with AEROSANA® VISCONN or AEROSANA® VISCONN FIBRE on both sides in the area where it is in contact with the subsurface.

Recommendations for subsurfaces that AEROSANA® VISCONN products can be used on can be found in the relevant application recommendations.

Delivery Form							
ID CODE	Forms of delivery	Length	Width	Sales unit	Piece/Container		
1AR01715	2 rolls	25m	150mm	1	90		



NEW ZEALAND 0800 PRO CLIMA (776 254) Technical: support@proclima.co.nz General: welcome@proclima.co.nz www.proclima.co.nz

AUSTRALIA 1800 PRO CLIMA (776 254) support@proclima.com.au welcome@proclima.com.au www.proclima.com.au

