



AEROSANA® VISCONN white

Sprayable Airtightness Sealant

AEROSANA® VISCONN white is a sprayable liquid airtightness membrane with a humidity-variable vapour resistance. Simply spray or paint it on for quick and effective sealing of connections, junctions and detailed features. It adheres to all standard materials, construction surfaces and can be plastered, painted and adhered to using pro clima TESCON® tapes, CONTEGA® tapes and ORCON® sealants. It is very useful for difficult junctions in mass timber, timber frame, commercial steel frames, concrete and masonry constructions.

- ✓ Simple spray or paint on application
- ✓ Particularly effective on junctions & detailed features
- ✓ Remains permanently elastic for long-term durability
- ✓ Sticks to all standard construction surfaces
- ✓ Can be plastered, painted, or adhered to

Tested for harmful substances
in accordance with



Based on the criteria of the Committee
for Health-Related Evaluation of
Construction Products at the German
Federal Environment Agency



11 2024



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au





AEROSANA® VISCONN white

Sprayable Airtightness Sealant

Technical Data

Material	Modified aqueous acrylate polymer dispersion
Colour	White
Coating application	0.2 – 1.0 mm wet film
sd value/ humidity variable	0.13 – 10.00m (0.65-50MNs/g)
Can be plastered / painted over	Yes, and all pro clima tapes can be adhered to it
Application temperature	5°C to 60°C
Temperature resistance	Permanent -40°C to 90°C (dried)
Coverage	Approx. 750ml/m ² , depending on applied thickness
Viscosity	10-15mPa·s

IMPORTANT INFORMATION

- For commercial and residential use
- Covers cracks and gaps up to 3mm
- We recommend using AEROSANA® FLEECE for gaps larger than 3mm.

PRODUCT DESCRIPTION

AEROSANA® VISCONN white is a high-quality, water-based acrylic dispersion paste that can be applied as a spray or using a brush. The sprayed-on liquid film forms a seamless, elastic airtight and vapour retarding protective layer once it has dried. Sticks to all standard construction materials, all pro clima membranes and membranes made from aluminium and paper.

WEATHER EXPOSURE

Suitable to use outdoors in protected areas.

APPLICATION NOTES

For use as a humidity-variable vapour retarder and airtight layer that can be applied as a spray or using a brush. The creation of joints to components such as windows, roofs, walls, ceilings and floors, and for panel joints on airtight wood-based panels (e.g. OSB) is easy and fast. It can also be used for strengthening sub-surfaces for renovation application. For gaps larger than 3mm, AEROSANA® FLEECE is recommended to be used.

Delivery Form					
ID CODE	Forms of delivery	Content	Coverage	Sales unit	Piece/Container
1AR01740	Bucket	10 Litre	750ml/m ²	1	45
1AR02749	Sausage	600 ml	750ml/m ²	12	720



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au

