



pro clima KAFLEX post

Cable Sealing Split-Patch

KAFLEX post is an airtight and weathertight sealing grommet made for quick and secure sealing of previously installed conduits and cables up to 20mm in diameter as well as non-round flat cables. KAFLEX is a beneficial component of all air barrier and weather resistive barrier systems. It is compatible with all pro clima membranes and underlays as well as rigid sheathings, rigid wall underlays and rigid air barriers (RAB). Strong and flexible, with integrated elastic adhesive band and simple-to-remove release paper, it ensures maximum productivity during installation. KAFLEX provides an airtight and water-tight pressure seal to the substrate and around the cable, for excellent performance under all conditions.

- ✓ Airtight connection for the life of the building
- ✓ Easy to work: extremely flexible and elastic
- ✓ Long-term durability
- ✓ 3 months of outdoor exposure
- ✓ Suitable for penetrations in façades and roof linings



01 2024



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au





pro clima KAFLEX post

Cable Sealing Split-Patch

Technical Data

| | |
|---------------------------|---|
| Material: | Special polypropylene fleece and perforated polyethylene foil |
| Adhesive: | Water-resistant SOLID adhesive |
| Release film: | Silicone-coated paper |
| Temperature resistance: | long term -40 °C to +90 °C |
| Installation temperature: | from -10 °C |
| Outdoor exposure: | up to 3 months |
| Colour: | Dark blue |
| Storage: | cool and dry |

IMPORTANT INFORMATION

- Suitable for previously installed cables with diameter of up to Ø 20 mm.
- Ideal for flat twin cables and twin and earth cables.
- Suitable for both internal and external applications.

PRODUCT DESCRIPTION

KAFLEX post is a cable sealing patch which forms a valuable part of your air barrier system. It has a split with PE foil which makes it easier to create airtight seals where existing cables or new flat cables penetrate membranes and/or smooth, non-mineral surfaces.

WEATHER EXPOSURE

This product is designed for use with external weather resistive barrier (WRB) systems and internal air barrier systems & will handle up to 3 months of outdoor exposure and still fulfil the intended use for air control.

APPLICATION NOTES

This product should be applied using the pro clima PRESSFIX tool to activate the pressure sensitive adhesive and guarantee a long-term durable seal.

Delivery Form

| ID CODE | LENGTH | WIDTH | QTY |
|----------|--------|--------|-----|
| 13635 | 140 mm | 140 mm | 5 |
| 1AR02187 | 140 mm | 140 mm | 10 |



NEW ZEALAND
0800 PRO CLIMA (776 254)
Technical: support@proclima.co.nz
General: welcome@proclima.co.nz
www.proclima.co.nz

AUSTRALIA
1800 PRO CLIMA (776 254)
support@proclima.com.au
welcome@proclima.com.au
www.proclima.com.au

