



pro clima CONTEGA® SOLIDO EXO-D

Window sealing tape for exterior use

CONTEGA® SOLIDO EXO-D is a full-surface adhesive window sealing tape with additional adhesive zone for exterior use. It is suited for exterior windtight joints that are resistant to driving rain. The adhesive zone on the fleece side allows for easier adhesion to windows and doors if applied before they are installed.

- ✓ Independently tested in accordance with MO-01/1 at IFT in Rosenheim, Germany
- ✓ Easy to work with thanks to the additional adhesive zone on the fleece side
- ✓ Can be taped to and plastered over directly
- ✓ Saves time: the joint is immediately resistant to driving rain
- ✓ Water-resistant SOLID adhesive



09 2026

Your local support

1800 PRO CLIMA (776 254)

Technical: support@proclima.com.au | General: welcome@proclima.com.au

www.proclima.com.au





pro clima CONTEGA® SOLIDO EXO-D

Window sealing tape for exterior use

Technical Data

Protective and covering fleece:	Polypropylene backing fleece and Polypropylene copolymer special film	
Adhesive:	Modified water-resistant SOLID adhesive	
Release film:	Split release silicone-coated PE sheet	
UV stability and outdoor exposure:	90 days	
Resistance to water penetrations	> 2,500 mm	EN ISO 811
Resistance to driving rain	PASS	ift, MO-01/1:2007-01, Abs. 5
Application temperature	Above -10 °C	
Temperature resistance:	-40 °C to +100 °C	

APPLICATION

There must be no water-repellent substances (e.g. grease or silicone) on surfaces where adhesives are to be applied. Subsurfaces must be sufficiently dry and stable; if necessary, they should be stabilised or renewed. Uneven mineral surfaces may need to be levelled with a smooth plaster finish.

It is the installer's responsibility to ensure the suitability of the subsurface; adhesion tests may be necessary in certain cases. Pre-treatment of the subsurface with TESCON PRIMER will improve the adhesive bond.

Once applied, the PRESSFIX tool must be used to pressure activate the adhesive to ensure long term adhesion. Weathertight seals resistant to driving rain can only be achieved if the sealing tape is installed free of folds and breaks.

For full application details and construction details library visit www.proclima.com.au.

Delivery form

ID CODE	LENGTH	WIDTH	Split release film	QTY
16135	30 m	80 mm	20 60 mm	1

Your local support

1800 PRO CLIMA (776 254)

Technical: support@proclima.com.au | General: welcome@proclima.com.au

www.proclima.com.au

